

RTCU NX-400 evo

Advanced Industrial M2M / IoT Gateway

State-of-the-art platform for tomorrows demanding applications

For Professional M2M / IoT Applications

The RTCU NX-400 evo has been designed for the most demanding M2M and Internet of Things applications that demands the absolutely most advanced product available on the market.

The RTCU NX-400 evo rests on the **RTCU M2M Platform**, that brings all the necessary tools together to develop, implement and maintain the most sophisticated M2M/IoT applications.

The **development task** is supported by the **free** RTCU IDE development environment complimented by a large and comprehensive documentation and application example library.

The RTCU Communication Hub is the corner-stone of the **communication infrastructure** ensuring reliable two-way device communication in any network environment.

Deploying and maintaining new application and firmware versions for devices in the field are handled by the powerful RTCU Deployment Server.

More than two decades of know-how in one product!

Experience and Know-how

For almost twenty years Logic IO has been committed to offer the most sophisticated platform for advanced and highly demanding M2M / IoT applications.

The RTCU NX-400 evo is the result of this accumulated experience combined with valuable feedback from hundreds of professional and mission critical applications by major organizations around the world.

RTCU products are deployed **underground, stationary, on the road, at sea, on the rail and in the skies!** - In any imaginable application and environment.



Device Advantages

- Powerful processor.
- Large memory capacity.
- Worldwide LTE Cat.4 Cellular Engine.
- WLAN.
- Bluetooth (Classic / LE).
- USB host port.
- Digital and analog input/outputs.
- Modbus expandable I/O.
- Graphical display with touchscreen.
- Multiple RS232/RS485 channels.
- Full CAN 2.0B support.
- Ethernet interface.
- 1-Wire bus.
- Digital audio with playback / record.
- Integrated battery backup.

Platform Advantages

- NX32L execution architecture.
- Secure platform.
- Hardware accelerated security.
- Free RTCU IDE development tool.
- Huge standard API.
- Open platform SDK.
- Comprehensive protocol support.
- Device Emulator.
- Sophisticated deployment tools.
- Fast and free email support.

World Leader in Advanced and Professional M2M / IoT Technology since 1999.

RTCU NX-400 evo Highlights

Advanced Industrial M2M / IoT Gateway

Platform:

- Based on the **RTCU M2M Platform**.
- **NX32L (NX32 for Linux) execution architecture**.
 - RTCU IDE development tool.
 - Operates under a full and highly optimized Linux variant.
 - Secure communication with TLS and hardware assisted encryption/authentication.
 - Open and extendable with Platform SDK.

Wireless Communication:

- **Worldwide LTE Cat. 4 Multi-Band Cellular Engine**.
- **Wireless LAN** (Wi-Fi).
- Classic and Low-Energy **Bluetooth**.
- **Optional**: Wireless M-Bus.

Wired Communication:

- 100 Mbps **Ethernet** LAN interface.
- **Full CAN 2.0B** controller with hardware filtering and multi-speed support.
- **1-Wire bus** for accessories such as ID-button reader, temperature sensors, etc.
- **USB host** port for expandability.
- **2 x RS232** channels and **2 x RS485** channels.

I/O Interfaces:

- **4 x analog inputs** and **4 x analog outputs** with 0..10 volt / 0..20 mA.
- **8 x digital inputs** and **8 x high-power** solid-state **digital outputs**.
- 4 digital inputs can be configured as **IEC62053-31 Class A** compliant.
- **Expandable I/O** with standard Modbus modules.

User Interaction:

- **Graphical 240x160 pixels White-on-Blue display**.
- **Touch-screen** with virtual buttons.
- **Digitized audio** with GSM / Speaker / Line-out and Microphone.
- **DTMF** support for Interactive Voice Response applications.
- High-speed **Mini-USB service-port** connector.

Storage:

- Internal **flash drive** with up-to 512 MByte capacity.
- **Persistent memory** and circular **datalogger**.
- Standard **SD-CARD** reader and **USB flash media**.




Services Available

Technical Support.
Application development support.
Maintenance.
Hardware support.
Warranty services.

Accessories

Modbus I/O extension modules.
HD Camera with video stream.
GPS receiver.
Antennas.
Cable parts.
1-Wire parts.
...and more.



Find out more and start developing today!

Learn more about the RTCU M2M platform and the NX32L architecture in the "The RTCU M2M Platform" data sheet.

To learn more about the technical details and usage of the RTCU NX-400 evo, please download the "RTCU NX-400 evo Technical Manual".

Also make sure to get the **FREE RTCU IDE** Development Environment, **RTCU Communication Hub** and the **Deployment Server** to get a hands-on experience how rapid development/deployment of game changing M2M/IoT applications were meant to be.

RTCU NX-400 evo Specifications

RTCU M2M Platform

- NX32 for Linux - NX32L.
- Fully NX32 compatible.
- Larger capacity and higher performance compared to NX32.
- Open and user-extendable API*.
- RTCU M2M Platform SDK.

NX32L Hardware Core

- Cortex-A5 32-bit ARM processor.
- Hardware floating point and DSP.
- 128 MByte LP-DDR RAM.
- 512 MByte NAND flash.
- 16 MByte NOR flash.
- 128 KByte SRAM with battery-backup.
- Real-time clock with battery-backup.

Security

- Embedded firewall.
- TLS/SSL support with full certificate management.
- TLS/SSL support for SMTP, MQTT, FTP, HTTP, RCH, and TCP/IP sockets.
- Hardware assisted strong encryption/authentication: AES-128, AES-192, AES-256, DES, TripleDES, HASH, RND and RSA signature.

Storage

- Persistent data flash.
- Non-volatile SRAM.
- Internal flash drive (Up-to 512 MByte).
- Circular datalogger.
- SD-CARD.
- USB flash media.

Cellular Engine

- **Multi-band LTE Cat. 4 [Worldwide]**
LTE FDD: 15 bands.
LTE-TDD: 4 bands.
WCDMA: 7 bands.
GSM: Quad-band.
- DTMF decoding / transmission.
- Digitized voice playback / IVR.
- External Mini SIM card-reader.
- Optional eSIM.

Wireless LAN

- WiFi at 2,4 GHz ISM bands.
- IEEE 802.11b/g/n/d/e/h/i.
- WPA/WPA2 certification.
- Up-to 150 Mbps.

Bluetooth

- Classic and Low Energy (LE).
- Bluetooth 2.1 + EDR up-to 3 Mbps
- Bluetooth 3.0 and 4.0 Dual mode.
- Intelligent co-existence with WiFi.

Optional Wireless

- Wireless M-Bus.
- ZigBee / IEEE 802.15.4.
- KNX RF.

Audio

- Fully digitized audio system.
- Transfer, store and play audio.
- Line and amplified speaker output.
- Microphone input.
- Digitized GSM audio.

Wired Communication

- 100BASE-T Ethernet interface.
- Full CAN2.0B with hardware filtering and multi-speed support.
- 2 x RS232. One with control signals.
- 2 x RS485.
- 1-Wire bus.
- USB host port.
- USB service/programming port.

User Interaction

- Dot-matrix LCD with 240x160 pixels.
- White-on-blue back-lit.
- Status-bar with information on all interfaces.
- Fully programmable with high-level functionality such as graphs, buttons, dialogs etc.
- Touch screen with virtual buttons.
- DX4i pro compatibility mode.
- 4 x bi-colour LED.
- DIP-switches.
- I/O configuration jumpers for analog mode.
- Virtual jumpers for RS485 and CAN termination
- Reset / recovery switch.



Logic IO Worldwide Headquarters

Holmboes Allé 14

8700 Horsens

Denmark

Phone: +45 7625 0210

Fax: +45 7625 0211

Commercial enquiries: sales@logicio.com

Technical support: support@logicio.com

www.logicio.com

RTCU NX-400 evo Specifications (continued)

Digital I/O Interface

- 8 x digital solid-state digital output.
Max. 36 volt / 1.5 A per. channel.
Short-circuit, ESD, Inductive kick-back protected up to 20 mH.
User supplied power.
- 8 x digital inputs.
Logic high: 8 to 40 VDC.
Logic low: -5 to 3 VDC.
Impedance: 3.3kohm @ 12V.
- 4 x IEC62053-31 Class A input.
- Digital input #1 can be used as ignition.

Analog I/O Interface

- 4 x analog inputs.
Range is 0..10VDC or 0..20 mA
Resolution: 12 bit
Accuracy: Typ. $\pm 0.3\%$ FSR @ 25°C
Impedance: 40 kohm (V)/504 ohm (C).
- 4 x analog outputs.
Range is 0..10VDC or 0..20 mA
Resolution: 12 bit
Accuracy: Typ. $\pm 0.3\%$ FSR @ 25°C.
- Protected against transients and low-pass filtered.

Electrical

- Operating voltage: 8 to 36 VDC.
- Short and reverse power protected.
- 5 VDC-out @ 300 mA.
- USB 5 VDC @ 500 mA.

Battery and Charger

- On-board 2Ah (nominal) Li-Ion battery.
- Intelligent charger with temperature throttle and sub-zero degrees support.
- Integrated battery temperature sensor.
- Support for larger external battery.

Power Management

- Low-power modes.
- Wait for Event: Timer, Digital input, Touch screen, RS232*, CAN, GSM*, Power change state.
- Wait for event, from: 2 mA@12V.
- Supervision of supply voltage / type.

External Interfaces

- SD-CARD slot with presence and write protect detection.
- Audio line-Out. 3.5mm mini-jack.
- Speaker-Out. 3.5mm mini-jack.
- Microphone. 3.5mm mini-jack.
- SIM-card slot for mini-SIM with lock and presence detection.
- Service-port (Mini USB-B).
- RJ45 for RS232 (EIA-561).
- RJ45 for LAN with LED indicators.
- USB host-port (USB-A receptable).
- SMA female connector for UMTS.
- RP-SMA connector for Wi-Fi/Bluetooth.
- Pluggable terminal blocks with 3.5 mm pitch and M2 screw:
Supply, I/O, CAN, RS485, RS232, 1-wire, DC-Out and external battery.

Expandable

- I/O expansion Modbus modules.
- GPS receiver.
- Additional Ethernet port.
- Additional RS232 / RS485 ports.
- Industrial USB hub.
- Camera with HD video streaming*
- Speaker and microphone.
- External battery pack.

Physical Characteristics

- Encapsulation: 9M DIN-rail (EN60715)
- Colour: Dark-Grey.
- Material: Self-extinguising blend PC/ABS.
- Approx. 465 gram without accessories.
- W 160.2 x H 89 (top) x D53.5 mm.
(without connectors and terminal blocks).

Environmental Specification

- Operating temperature: -30 to 60°C.
- Battery charge temperature:
-10 to 45 °C
- Recommended storage temperature:
0 to 45°C.
- Humidity: 5..90% (non condensing).
- Ingress Protection: IP20 .

Approvals

- 2014/53/EU Radio Equipment Directive.
- 2014/30/EU EMC Directive
- 2011/65/EU RoHS Directive.

Warranty

- Two-years return to factory parts and labor.
- Optional warranty up to 5 years.
(restrictions apply).



Logic IO Worldwide Headquarters

Holmboes Allé 14
8700 Horsens
Denmark
Phone: +45 7625 0210
Fax: +45 7625 0211
Commercial enquiries: sales@logicio.com
Technical support: support@logicio.com
www.logicio.com

Models Available

SKU: RT-NX400-EVO